

Diesel Engine Oil

Premium Mineral Technology

SELANDIA DX6

PRODUCT DESCRIPTION:

Selandia DX6 is an advanced mineral high performance heavy duty engine oil that helps extend engine life and improve fuel economy in modern diesel engines operating in severe conditions, it maximizes engine performance in the latest US, European and Japanese heavy-duty diesel engines including severe applications such as high loads and multi-trailer operations.

Applications:

Selandia DX6 is a mixed fleet motor oil recommended for new advanced diesel powered engines in trucks, marine industries, heavy duty construction equipment, mining equipment, farm vehicles, passenger cars, operation under severe conditions and subjected to wide variations in climatic conditions, for on-highway in both high speed/high load and stop-and-go conditions. They are also recommended for gasoline engines in pick-up trucks and sports utility vehicles.

Meets and Exceeds Performance Levels:

- API Service Category CJ-4 / SM
- ACEA E9/E7
- Caterpillar ECF-3
- Cummins CES 20081
- Renault RLD-3
- Mack EO-O Premium Plus
- MAN M3575
- MB 228.31
- Volvo VDS-4.

Features:

- Fights oil thickening due to its unique additive system, it delivers superior viscosity stability, resulting in better fuel efficiency.
- Prevents piston deposits by minimizing harmful deposits, resulting in lower oil consumption.
- Fights contaminants, resulting in longer oil drain intervals.
- Prevents wear and corrosion by providing a robust oil film, enhancing the life of critical engine components
- Formulated with lower levels of Sulphated Ash, Phosphorous and Sulphur than conventional oils to maintain the efficiency of exhaust after treatment systems eg. DPF or DPD
- Fights soot abrasive wear, improving engine power all the way through the oil drain

Typical Properties:

PARAMETERS	TEST METHOD	UNIT	Selandia DX6		
			15W-30	15W-40	20W-50
Grade			15W-30	15W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	89.1	112.0	170.0
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	12.0	15.40	20.2
Viscosity Index (min)	ASTM D-2270	-	128	145	138
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm3	0.870	0.870	0.878
Flash Point (min)	ASTM D-92	°C	234	230	240
Pour Point (max)	ASTM D-97	°C	-33	-33	-24
TBN	ASTM D-2896	Mg KOH/g	8	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	6700 (-20)	6700 (-20)	9000(-15)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website