

Gasoline Engine Oil

Premium Mineral Technology

XTEND 2T RACE

PRODUCT DESCRIPTION:

Xtend 2T RACE is a lubricant that is suitable for 2-stroke motorcycles, scooters and mopeds. It is designed to provide excellent performance in two stroke air-cooled powered engines. Race 2T is a lubricant that is suitable for relatively un-demanding day-to-day driving conditions. It's composition is perfectly compatible with lead-free fuels. This is a high technology product combining a perfect balance of highly refined paraffinic base stocks and the latest additive's technology. It is specially formulated for use in oil injected as well as premixed gasoline/oil lubricated engines. It's increased performance provides protection against exhaust emissions and engine carbon deposits.

Applications:

is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended.

Meets and Exceeds Performance Levels:

- API Service Category TC
- JASO FD
- ISO-L-EDG

Features:

- Provides piston scuffing protection and reduces smoke
- Thermal and oxidation stability
- Specially formulated to avoid spark plug fouling
- Perfectly adapted to unleaded fuel
- Protection against pre-ignition problems

Typical Properties:

PARAMETERS	TEST METHOD	UNIT	XTEND 2T RACE	
Grade			20	30
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	60	87
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	9	12
Viscosity Index (min)	ASTM D-2270	-	127	129
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm3	0.880	0.880
Flash Point (min)	ASTM D-92	°C	130	130
Pour Point (max)	ASTM D-97	°C	-24	-24
TBN	ASTM D-2896	Mg KOH/g	2	2
COLOR	ASTM D-1500	-	BLUE	BLUE

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website