

Gasoline Engine Oil

Premium Mineral Technology

## XTEND 4T RACE

**PRODUCT DESCRIPTION:**

Xtend 4T RACE is recommended for high-performance 4T motorcycles that delivers high power efficiency and acceleration. It exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions. It is excellent in maintaining high engine power and fuel economy with longer drain interval.

**Applications:**

- Recommended for all scooters and motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

**Meets and Exceeds Performance Levels:**

API Service Category SJ and JASO MA2

**Features:**

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

**Typical Properties:**

PARAMETERS	TEST METHOD	UNIT	XTEND 4T RACE		
Grade			10W-30	10W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	76.2	100.2	170.0
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	11.9	14.9	20.2
Viscosity Index (min)	ASTM D-2270	-	152	156	138
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm3	0.869	0.870	0.878
Flash Point (min)	ASTM D-92	°C	230	230	240
Pour Point (max)	ASTM D-97	°C	-36	-36	-24
TBN	ASTM D-2896	Mg KOH/g	7	7	7
CCS, (°C)	ASTM D-5293	m.Pa.S	6600(-25)	6700(-25)	9000(-15)

**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website