

Gasoline Engine Oil

Premium Mineral Technology

XTEND GX-6000

PRODUCT DESCRIPTION:

XTend GX-6000 is a superior quality multi-grade oil formulated with highly refined base stocks and premium additives technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.

Applications:

- Suitable for gasoline/diesel/CNG/LNG engines.

Meets and Exceeds Performance Levels:

- API Service Category SJ/CF

Features:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Excellent protection against sludge and varnish deposits

Typical Properties:

PARAMETERS	TEST METHOD	UNIT	XTEND GX-6000		
Grade			15W-30	15W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	89.1	112.0	170.0
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	12.0	15.40	20.2
Viscosity Index (min)	ASTM D-2270	-	128	145	138
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm3	0.870	0.870	0.878
Flash Point (min)	ASTM D-92	°C	234	230	240
Pour Point (max)	ASTM D-97	°C	-33	-33	-24
TBN	ASTM D-2896	Mg KOH/g	7	7	7
CCS, (°C)	ASTM D-5293	m.Pa.S	6700 (-20)	6700 (-20)	9000(-15)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website