

Gasoline Engine Oil

Premium Mineral Technology

XTEND GX-7000

PRODUCT DESCRIPTION:

XTend GX-7000 are premium quality mineral oils for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is suited to turbo-charged engines and is also adapted to vehicles equipped with catalytic converter and using unleaded.

Applications:

- Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles, light truck gasoline engines. Four stroke gasoline engines and portable power equipment.

Meets and Exceeds Performance Levels:

- API Service Category SL/CF
- ACEA A3/B3
- MB 229.1
- VW 501 01 / 505 00

Features:

- High viscosity index
- Excellent viscosity stability
- Excellent detergency and dispersancy
- Very high antiwear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties

Typical Properties:

PARAMETERS	TEST METHOD	UNIT	XTEND GX-7000		
			15W-30	15W-40	20W-50
Grade			15W-30	15W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	89.1	112.0	170.0
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	12.0	15.40	20.2
Viscosity Index (min)	ASTM D-2270	-	128	145	138
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm3	0.870	0.870	0.878
Flash Point (min)	ASTM D-92	°C	234	230	240
Pour Point (max)	ASTM D-97	°C	-33	-33	-24
TBN	ASTM D-2896	Mg KOH/g	8	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	6700 (-20)	6700 (-20)	9000(-15)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website