

Gasoline Engine Oil

Premium Semi-Synthetic Technology

XTEND GX-9000

PRODUCT DESCRIPTION:

Xtend GX-9000 are particularly well-suited for hot countries with medium to high temperatures. These oils can be used with petrol or diesel engine technologies without particulate filters and engines built prior to 2004. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and better low temperature performance over the life of the oil.

Applications:

- Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles, light truck gasoline engines. Four stroke gasoline engines and portable power equipment.

Meets and Exceeds Performance Levels:

- API Service Category SM/CF
- MB 229.1
- ACEA A3/B4
- VW 501 01 / 505 00

Features:

- Enables fast and easy start in extreme temperature conditions
- Particularly recommended for urban driving
- Oil film able to withstand high operating temperatures
- Protects engines against deposits • Standard drain interval

Typical Properties:

PARAMETERS	TEST METHOD	UNIT	XTEND GX-9000	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	76.2	100.2
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	11.9	14.9
Viscosity Index (min)	ASTM D-2270	-	152	156
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm3	0.869	0.870
Flash Point (min)	ASTM D-92	°C	230	230
Pour Point (max)	ASTM D-97	°C	-36	-36
TBN	ASTM D-2896	Mg KOH/g	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	6600(-25)	6700(-25)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website